

BREAK SHARP CORNERS MAY BE EITHER CHAMFER OR RADIUS FROM 0.2 mm MIN. TO 1.0 mm MAX.

THIS DRAWING IS A SOLE PROPERTY OF M & M Ltd. IT SHOULD NOT BE REPRODUCED IN ANY FORM OR BY ANY MEANS WITHOUT THEIR CONSENT

D

C

B

A

D


C

B

A

REFER DRAWING :- 008032636U01

REF PART NO: 007537394C91

UNSPECIFIED TOLERANCES FOR PART		SURFACE FINISH SYMBOLS:ISO-1302		 MAHINDRA & MAHINDRA LTD. FARM DIVISION, INDIA								
FORMING TO FORMING	UPTO 500 ±0.5 ABOVE 500 ±0.8	WELDING SYMBOLS:IS813										
CD BETWEEN HOLES	IN ONE PLANE ±0.2 IN DIFF PLANES±0.5	DO NOT SCALE ALL DIMENSIONS ARE IN mm		<SC> COUNT : 0		NAME	DATE	PROJECT CODE:				
FORM TO PIERCE	±0.5			<CC> COUNT↙ 0		DSNR	AR	07-06-2023	ER NUMBER: ER23C0000228			
HOLE SIZES	+0.2/-0			WEIGHT(kg) : 1.71		CHKR	NVC	07-06-2023	DESCRIPTION :			
SLOT SIZES	±0.8			S/F AREA(cm²): 700		APPR	DS	07-06-2023	CHANNEL SUPPORT RH			
FLANGE WIDTH	+1.0/-0.7			MATERIAL:						PART NUMBER :		CL:
JOGGLE DEPTH	+0.3/0									008032652U01		NA
UNSPECIFIED TOLERANCES FOR PART & ASSEMBLY						DWG.SIZE : A4		SCALE :		1:1	SHEET: 1 OF 1	
GENERAL TOLERANCES	UP TO 300 ±0.8 ABOVE 300 ±1.0											
ANGULAR TOLERANCE	±1°											